
MULTIGRASS

DESCRIPTION

Multigrass is a low odour solvent based trowel applied adhesive for one way bonding of synthetic grass (Astrograss) on concrete or timber. Bostik Multigrass has an exceptionally strong initial grab and good gap filling to ensure the best possible bond to all surfaces. It has an excellent water resistant bond which is important for outdoor applications. Early rain onto the bonded membranes will not affect the bond even if the adhesive becomes flooded.

CAUTION

Bostik Multigrass Adhesive contains solvents and is highly flammable. All naked flames must be extinguished before starting work. The work area must be well ventilated. If working in enclosed areas where the ventilation is limited, an activated carbon mask, suitable for solvent should be worn.

APPLICATION

Thoroughly clean the floor, making sure all loose dirt and dust is removed. The sub-floor must be dry and free from oil, grease, dust or any contaminant.

Apply an even covering of Multigrass with a notched trowel to ensure the correct coverage. Only apply adhesive to an area that can comfortably be covered in 15 minutes. Synthetic grass should be laid into the adhesive immediately after adhesive application. Pay particular attention to lay the synthetic grass before the adhesive skins up too much to prevent proper adhesive transfer. Apply even pressure using a heavy roller to ensure maximum adhesion. Bostik Multigrass should not be applied to a wet surface although a good bond can be obtained on surfaces recently dried out by the sun. As long as there is a good initial wetting out of the surface (if the adhesive film sticks well to the surface during trowelling) a good bond strength will be obtained.

IMPORTANT : Coverage is approx 1.5 – 4 square meters / litre. This ranges from very “rocky” to dead smooth floors. Skimping on adhesive is not sensible as the bond strength will be compromised.

STORAGE

Store in cool, dry conditions out of direct sunlight below 25°C and away from naked flame or sources of heat.

Wellington Site (Factory & Admin)
Auckland Site

19 Eastern Hutt Road, Wingate, Lower Hutt
148 Pavilion Drive, Airpark II, Auckland Airport

Ph ++64 4 567 5119
Ph ++64 9 257 5847

Fax ++64 4 567 5412
Fax ++64 9 257 3588

www.bostik.co.nz

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.co.nz

TRANSPORT

Proper Shipping Name:	ADHESIVES
Hazard Class:	3
UN Number:	1133
Hazchem Code:	3[Y]E
Packaging Group:	11

PACKAGING

20 Litres

SHELF LIFE

12 months if stored in cool, dry conditions in original, unopened containers.

VERSION

Version 3.1	5 th August 2011
-------------	-----------------------------