

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LUMBERJACK 5 MINUTE PU WOOD ADHESIVE GEL

Product code: 5MINPU3

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: pault@everbuild.co.uk

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20

Classification under CLP: Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335; -: EUH204

Most important adverse effects: Irritating to eyes, respiratory system and skin. Limited evidence of a carcinogenic effect.
May cause sensitisation by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

2.2. Label elements

Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H351: Suspected of causing cancer.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

SAFETY DATA SHEET

LUMBERJACK 5 MINUTE PU WOOD ADHESIVE GEL

Page: 2

H373: May cause damage to organs through prolonged or repeated exposure.

EUH204: Contains isocyanates. May produce an allergic reaction.

Signal words: Danger

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard



Precautionary statements: P337+313: If eye irritation persists: Get medical attention.

P501: Dispose of contents to hazardous waste.

P342+311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

P405: Store locked up.

P102: Keep out of reach of children.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P332+313: If skin irritation occurs: Get medical advice.

P285: In case of inadequate ventilation wear respiratory protection.

P321: Specific treatment (see information on this label).

P362: Take off contaminated clothing and wash before reuse.

P271: Use only outdoors or in a well-ventilated area.

P202: Do not handle until all safety precautions have been read and understood.

P312: Call a POISON CENTER or doctor if you feel unwell.

P264: Wash hands thoroughly after handling.

P261: Avoid breathing vapours.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical advice.

Label elements under CHIP:

Hazard symbols: Harmful.



Risk phrases: R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitisation by inhalation and skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

[cont...]

SAFETY DATA SHEET

LUMBERJACK 5 MINUTE PU WOOD ADHESIVE GEL

Page: 3

Safety phrases: S2: Keep out of the reach of children.
S25: Avoid contact with eyes.
S22: Do not breathe dust.
S23: Do not breathe vapour.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37: Wear suitable protective clothing and gloves.
S46: If swallowed, seek medical advice immediately and show this container or label.
S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.

2.3. Other hazards

PBT: This product is not identified as a PBT/VPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-966-0	101-68-8	Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

[cont...]

SAFETY DATA SHEET

LUMBERJACK 5 MINUTE PU WOOD ADHESIVE GEL

Page: 4

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Allow product to solidify and remove it by mechanical means. Remove uncured foam with acetone Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

[cont...]

SAFETY DATA SHEET

LUMBERJACK 5 MINUTE PU WOOD ADHESIVE GEL

Page: 5

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m3	0.07 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Colourless

Odour: Barely perceptible odour

Evaporation rate: Negligible

Solubility in water: Insoluble

Also soluble in: Most organic solvents. in uncured state. Use EVERBUILD FOAM EATER to remove cured product

Viscosity: Highly viscous

Kinematic viscosity: 300000mpas

Boiling point/range°C: 200

Flash point°C: not applicc.

Autoflammability°C: >200

Relative density: 1.1

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET

LUMBERJACK 5 MINUTE PU WOOD ADHESIVE GEL

Page: 6

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat. Moist air. Humidity. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of hydrogen cyanide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

ORL	MUS	LD50	2200	mg/kg
ORL	RAT	LD50	9200	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT INH DRM	Hazardous: calculated
Sensitisation	INH DRM	Hazardous: calculated
Repeated dose toxicity	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

[cont...]

SAFETY DATA SHEET

LUMBERJACK 5 MINUTE PU WOOD ADHESIVE GEL

Page: 7

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity. Not dangerous to ozone layer (1999/45/EC)

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J L47 of 16/2/2002): 08 05 01 (waste isocyanates)

Waste code number: 08 04 09

Disposal of packaging: Waste material code packaging (91/689/EEC); Council decision 2001/118/EC, O.J L47 of 16/2/2001) 15 01 10 (packaging containing residues of or contaminated by dangerous substances)

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH204: Contains isocyanates. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

[cont...]

SAFETY DATA SHEET

LUMBERJACK 5 MINUTE PU WOOD ADHESIVE GEL

Page: 8

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitisation by inhalation and skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.